



Viewing Station

In a compact form factor, the perfect **viewing** complement to a CheckVideo solution.

Reliable protection has never been this simple.

The **CheckVideo Viewing Station** (V1101) is a local viewer for on-site cameras. The V1101 is equally suited for guard desks, reception areas and command-center display walls and is compatible with standard HDMI displays. Matrix views from 4 to 36 live H.264/H.265 streams can be programmed for display. Any camera view can be displayed full-screen for detailed review. The layout can be modified and views can be saved for instant recall. Camera tours are also available.

The Viewing Station is a managed device and is remotely configured through the CheckVideo Video Management System (CVMS). V1101 also receives and applies software updates automatically and requires no on-site maintenance. It continues to function and display video from local cameras even during loss of Internet connectivity.

SYSTEM

Fanless embedded computer with media engine Embedded Linux OS with auto-updates

Display

Port 1: HDMI 1.4, 1080p resolution Port 2: HDMI 2.0, 4K resolution

Network

Integrated 10/100/1000 Ethernet Network connection

ENVIRONMENT

Operating temperature

 $0^{\circ}\,\text{C}$ to $40^{\circ}\,\text{C}$

Storage temperature

-10° C to +60° C

ORDERING

Model: V1101 KPN: 202011

VIDEO

Inputs

IP video from up to 36 cameras. Supports CheckVideo cameras, Gateways and ExpressHD Recorders

Configuration

Remote Management and view configuration 2x2, 3x3, 4x4,5x5 or 6x6 matrix view

MECHANICAL

Dimensions

6.1" x 5" x 1.75"(154.9 mm x 127 mm x 44.45 mm)/VESA mount

Power

12V DC back panel power connector/12V, 36W power supply included

BACK PANEL

