



# 12 MEGAPIXEL PANORAMIC INDOOR/OUTDOOR CAMERA

S1812



The CheckVideo 12MP Panoramic Indoor/Outdoor Camera (S1812) provides coverage equivalent to four cameras in a single weatherproof package. Featuring a wide-angle lens coupled with an industry-leading 12MP sensor, the S1812 also supports de-warped 360 degree panorama in ceiling mode or a 180 degree panorama in wall mode. The camera includes edge de-warping capability and multiplexing to provide a quad view in a single stream.

The S1812 is a complete video surveillance system with built-in 30-day HD recording and advanced video analytics. The camera can be viewed using simply a web browser, through CheckVideo's Cloud VMS service, that also enables digital pan, tilt and zoom functions. With just a single network cable required, the S1812 is easy to install. It is the perfect solution for cost-effective surveillance of outdoor lots, hallways, and retail stores.

## CAMERA



### **COST-EFFECTIVE SURVEILLANCE**

4 camera views in a single package.



### **FLEXIBLE PANORAMA MODES**

With edge de-warping. Includes support for 360° views in single stream for ceiling mount or panoramic 180° views in wall mount mode.



### **OUTDOOR RATED**

Includes an IP 66 weatherproof housing with built-in IR illumination.

## VIDEO MANAGEMENT



### **CLOUD FEDERATION**

All cameras across multiple locations are federated into a single unified system that scales from one camera to thousands of cameras. This drastically reduces system cost and complexity.



### **WEB AND MOBILE VIEWING**

Use a web browser to log into the cloud VMS and view live, playback recorded video or use our advanced search engine to find video in seconds. Our mobile apps also put this capability within easy reach.



### **CYBER-SECURITY INCLUDED**

Hacker-proof and secure using 2048 bit certificates. Built-in firewall and encrypted communication for added security.

## CAMERA

**Image Sensor** Sony 1/1.7" Progressive CMOS  
**Effective Pixels** Up to 12 megapixels

**Minimum Illumination Color** Color 1 lux, B/W with IR: 0 lux up to 20 ft.

## VIDEO

**Video Compression** H.264/H.265 Baseline/Main Profile/High Profile

**Edge De-warping** 360° ceiling mount, 180° wall mount view, quad view

MODE	VIEW	RESOLUTION				
Wall	180°	4000x2000				
Ceiling Dual Panorama	180°	4000x3000				
	180°					
Quad	<table border="1" style="width: 100%; height: 100%;"> <tr> <td style="width: 50%; height: 50%;"></td> <td style="width: 50%; height: 50%;"></td> </tr> <tr> <td style="width: 50%; height: 50%;"></td> <td style="width: 50%; height: 50%;"></td> </tr> </table>					3000x3000

## VIDEO MANAGEMENT

**Cloud VMS** Works with CheckVideo Cloud VMS. Offers 100% web and mobile viewing, advanced search and cloud backup. No NVR needed on-site.

**Alarm Monitoring Integration** Bold Manitou, Micro Key MKMS, SIMS II/III, Immix®, SGS-stages

## ANALYTICS

**Engine** Auto-calibrating analytics with tracking and classification engine for people and vehicles. Rejects clutter from environment and illumination changes.

**Analytics** Person Detection, up to 100 feet  
 Vehicle Detection, up to 150 feet  
 Zone Violation  
 Loitering Person  
 Stopped Vehicle

**Video Alarm** 10-second video clip generated upon trigger of alarm; contains 2-4 seconds of pre-alarm video

## NETWORK

**Wired** RJ-45, 1Gbps Ethernet

**Protocols** ARP, IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, DHCP

## DVR

**Resolutions** 12MP or 2MP

**Recording** Built-in recording up to 30 days of continuous 24/7 recording at 2MP.

**Web Player** Live streaming compatible with web browsers and mobile devices

## GENERAL

**Dimensions** Ø 130.1 x 38.3 mm (Ø 5.12 x 1.51 in.)

**Operating Conditions** -30°C ~ 55°C (-22°F ~ 131°F)  
 Humidity: 10% ~ 90%, no condensation

**Power Source/Consumption** PoE IEEE802.3af, class 0, max 12.95 watt, DC 12V, max 11.16 watt

**Approvals** CE / FCC / IP66/IK103/ NDA Compliant

**S1812 Part Number** 202070

**25° Wall Mount** 202054

**Mount Cap** 202051

**Outdoor Wall Bracket** 201581

**Junction Box Adapter** 202050